



COLOR RITE ,INC.
 600 South Ranchwood Blvd.
 Yukon, Oklahoma 73099
 405-354-3644

LEEDS VOC LEVELS ALLOWANCES

COLOR RITE Acrylic Sealant Adhesive Caulk

LEEDS CRITERIA

SEALANTS	CURRENT VOC LIMIT
ARCHITECTURAL	250g/L

Rule #1168 Adhesive and Sealant Applications

Definition (67)

Sealant is any material with adhesive properties that is formulated primarily to fill, seal, or waterproof gaps or joints between two surfaces.

Sealants include sealant primers and caulks.

EQc4.1:Low-Emitting Materials, Adhesives and Sealants

LEEDS VOC content of sealant and adhesive products:

If a sealant/adhesive is used to bond to similar or dissimilar substrates the sealant/adhesive the VOC content below is allowed.

LEEDS BAAQMDR Reg. 8 Rule 51 >250g/L

LEEDS SCAQMD Rule # 1168 >250g/L

MSDS COLOR RITE Acrylic Sealant Adhesive Caulk

Section IX. Physical and Chemical Properties

***** **Line 11** Volatile Organic Content: 22 grams / liter (Liter of caulk weighs 1209 grams.)

Line 12 Volatile Organic Content: *Less H₂O* 14.74 grams / liter