



**COLOR RITE ,INC.**  
 600 South Ranchwood Blvd.  
 Yukon, Oklahoma 73099  
 405-354-3644

**100% RTV SILICONE CAULK/ SEALANT**

**LEEDS VOC LEVELS ALLOWANCES**

**COLOR SIL** 100% RTV Silicone Caulk

**LEEDS CRITERIA**

<b>SEALANTS</b>	<b>CURRENT VOC LIMIT</b>
ARCHITECTURAL	250g/L

**Rule #1168 Adhesive and Sealant Applications**

**Definition (67)**

Sealant is any material with adhesive properties that is formulated primarily to fill, seal, or waterproof gaps or joints between two surfaces.

Sealants include sealant primers and caulks.

EQc4.1:Low-Emitting Materials, Adhesives and Sealants

**LEEDS VOC content of sealant and adhesive products:**

If a sealant/adhesive is used to bond to similar or dissimilar substrates the sealant/adhesive the VOC content below is allowed.

LEEDS SCAQMD Rule # 1168 >250g/L

LEEDS BAAQMDR Reg. 8 Rule 51 >250g/L

**MSDS COLOR SIL** 100% RTV Silicone Caulk

**Section IX.** Physical and Chemical Properties

\*\*\*\*\* **Line 18** Volatile Organic Content: 29.86 grams / liter